5 Bray COMMERCIAL

Bray Controls Commercial Division 13788 West Road, Suite 200A Houston, Texas 77041

BCDSales@Bray.com Phone: 1-888-412-2729 www.braycommercialdivision.com © 2021 Bray International, Inc.

12/01/22



For ST2 Ball Valves with VA Series Actuators

Description

The Bray Small Weather Shield is an industrial grade, convenient, and cost-effective method of protecting actuators from the harsh elements and washdowns, not just weather.

Features

- · Enclosure constructed of impact-grade plastic that provides excellent impact resistance.
- · Fully Enclosed Design Protects the electric actuator from corrosion, rain, freezing rain, sleet, and snow.
- Strain Relief Conduit Fittings Protect the electric actuator from • damage by preventing tension on the electrical connection.


Benefits


- UV inhibitors prevent cover from becoming brittle or damaged by the sun or other environmental elements.
- Translucent Cover provides an unobstructed view of the electric actuator without having to disassemble the enclosure.

Specifications					
Top Cover	Transparent UV resistant polycarbonate plastic				
Enclosure Seal	Nitrile				
Body	UV resistant polycarbonate plastic				
Cover Gasket	Polyurethane				
Electrical Connections	Strain relief conduit fittings with 1/2 in. (13 mm) National Pipe Straight Mechanical (NPSM) exit				
Ambient Temp. Limits	-40 to 176°F (-40 to 80°C)				
Dimensions	See Below				
Protection Rating	NEMA 4X, IP66				
Weight	4.2 lb (1.9 kg)				
Warranty	5 Years limited from time of shipment				




Model Number	Description - Actuators Covered			
M9000-342	ST2 Direct Mount (VA Series) Actuators			





Dimensions - Small Weather Shield - in. (mm)								
in.	mm	А	В	С	D	E		
.5	15	7-1/2 (191)	9-29/64	11-1/16 (281)	8-5/8 (219)	4-23/32 (120)		
.75	20	7-1/2 (191)						
1	25	7-37/64 (192)						
1.25	32	8 (203)	(240)					
1.50	40	8-11/64 (208)						
2	50	8-11/32 (212)						





13788 West Road, Suite 200A Houston, Texas 77041